

Wally's Wowzer

By: Wally Miechowski




Materials:

Hook: Size 2/0 Stainless Steel Mustad 34007
Thread: Fine clear Uni-mono
Gill: Red thread
Belly: White bucktail
Lateral Line/Tail Flash: Flashabou
Wing: White bucktail
Over-wing: Peacock herl or darker bucktail
Eye: Dumbbell eyes or similar
Adhesives: Hard As Nails

STEP 1:

Remove barb - sharpen hook, place hook in vise point down, wrap mono from behind the hook eye back to a point about 1/3 of the way down the bend of the shank and back again to the eye. Place weighted eye on top of the shank close behind the hook's eye. Secure tightly, making sure eyes are level and straight. Glue all wraps.



STEP 2:

Cut a clump of white bucktail. Tie in the bucktail tightly behind the eye on top of the hook shank, and tie all the way back and slightly down the bend of the hook. When tying keep "UP" pressure on the bucktail to insure it remains on top of the hook. Tie off and cut mono, remove from the vise, lay hook on level surface point up, make sure bucktail has not rotated around the hook shank, if so straighten so you can see the bare shank from the hook eye to the point. Replace in vise, using red thread tie in gill plate



behind the lead eye for approximately 1/4 ". Tie off the thread, cut and clue all wraps behind the eye.

STEP 3:

Lateral line/Tail flash

With hook pointing up, cut approx 15 to 20 strands of flashabou full length. Double material evenly on thread making 1 twist in the material, You now have 2 equal lengths of material, keep separated. Make about 10 twists directly behind the hook eye, then take both lengths of material back along the shank of the hook, one on each side of the hook to the loose bucktail. Pinch tightly, wrap mono back along the hook shank while keeping slight upward pressure. At this point you are creating both a lateral line and tail flash, while evenly covering the bare bottom of the hook shank. Advance thread back to hook eye and glue the lateral line.



STEP 4:

Tying the Wing - Tie a clump of white bucktail directly behind the hook eye, wrap securely and glue while holding the material up at an angle to match the up-angled tail and flash material. (Step 4 and 5 can be accomplished with the fly in the vise or as a helpful hint try the following; straighten the flat metal tail of a strong alligator clip, place alligator clip in vise with the fly held by the clip.)



STEP 5:

Add a contrasting color or peacock hurl. Complete by holding all materials tied on top of the eye slightly upward while placing several drops of glue on top and on both sides of the eye down to the red gill plate. Be careful the glue does not travel too far up the material to the hook point so as not to interfere with hook set. Although not necessary, Hard As Nails may be applied.



The fly is finished and ready to be fished.